

PRINT THIS PAGE 

1500 rpm 50 Hz – cos ϕ 0,8 230V-400/230V 1800 rpm 60 Hz – cos ϕ 0,8 voltage on request

FUSTEQ  **SCANIA**



STANDARD EQUIPMENT

- Lifting eye
- Fully bunded fuel tank
- Integrated fuel tank
- Cooling system with electric fans controlled by Inverter
- Air filter
- Manual control panel with circuit breaker
- Distribution panel with output sockets standard up to 30 A
- 12/24V battery
- Ultra-silent canopy
- Forklift guides

DIESEL Water Cooled

> ALTERNATORS

LEROY-SOMER
Nidec

STAMFORD



meccalte

 **MarelliMotori**
Power generation

MODEL	kVA LTP	kVA PRP	kVA LTP	kVA PRP	Engine	Regulator	Cylinder	cm3	kWm 1500 rpm		kWm 1800 rpm		(l/h) 1500 rpm	Fuel saving (l)	(l/h) 1800 rpm	Fuel saving (l)	Aspiration	Standard panel	Synchronising control panel (option)	dB(A) (+) 7 m	Tank l	AdBlue tank l	Dimensions			Kg
									Mechanical radiator	Electric radiator	Mechanical radiator	Electric radiator	Cons. 70%	In 1000 h operation	Cons. 70%	In 1000 h operation							L	W	H	
SA300FQ V	300	275	308	280	DC09 320A 02-62	E	5	9300	238	239.6	241	242.6	41.12	480	42.42	480	T	AUS7310	SCP8610	59	70	1000	540	113	227	6000
SA330FQ V	330	300	335	305	DC09 320A 02-63	E	5	9300	259	260.6	262	263.6	44.42	480	46.12	480	T	AUS7310	SCP8610	59	70	1000	540	113	227	6040
SA360FQ V	363	335	385	350	DC09 320A 02-64	E	5	9300	283	284.6	297	298.6	50.12	480	52.52	480	T	AUS7310	SCP8610	59	70	1000	540	113	227	6990
SA390FQ V	390	355	400	365	DC13 320A 02-61	E	6	12700	301	303.6	308	310.6	50.1	800	53.2	800	T	AUS7310	SCP8610	61	168	2000	500	210	240	8340
SA450FQ V	445	405	456	415	DC13 320A 02-62	E	6	12700	344	346.6	351	353.6	57.8	800	60.5	800	T	AUS7310	SCP8610	61	168	2000	500	210	240	8540
SA500FQ V	500	455	510	465	DC13 320A 02-63	E	6	12700	387	389.6	394	396.6	63.7	800	67.3	800	T	AUS7310	SCP8610	61	168	2000	500	210	240	8630
SA506FQ V	550	500	550	500	DC16 320A 02-62	E	8V	16400	426	431.6	426	441.6	64.4	1600	68.5	4800	T	AUS7310	SCP8610	62	160	2000	500	210	240	8980
SA550FQ V	600	550	627	570	DC16 320A 02-63	E	8V	16400	468	473.6	468	483.6	77.5	1600	81.3	4800	T	AUS7310	SCP8610	62	160	2000	500	210	240	9050

Legend: N= natural T= turbo

> CONTROL PANEL



TECNOGEN S.p.A.

Strada per Ponte Riglio, 25
29010 Pontenure (Piacenza) Italy

P.IVA/CF 01126350337

ITALY SALES DEPARTMENT

Tel: +39 0523 512401

Fax: +39 0523 504453

E mail: italy@tecnogen.com

EXPORT DEPARTMENT

Tel: +39 0523 512440 Fax: +39 0523 504453

E mail: export@tecnogen.com